



| | |
|----------------------------|-----------------|
| PRODUCT DATA SHEET | Page 1 of 2 |
| | Revision: 2 US |
| RD-FLEECE OCTAGONAL | Date: 2/15/2007 |
| | |

DESCRIPTION OF THE PRODUCT

USE: Reinforcement mesh for the bridging of active cracks as part of the RD waterproofing coating systems for roofs, decks and walls.

FEATURES: Good bridging ability of cracks. Good resistance to UV, acids and alkali.

SUBSTRATES: All substrates as adapted by the RD Coating systems for roofs, decks and walls.

SYSTEM:

APPLICATION INSTRUCTIONS

PREPARATION OF THE SUBSTRATE:

APPLICATION CONDITIONS:

APPLICATION MEANS:

DILUTION:

CLEANING OF TOOLS:

COMPOSITION: 100% Polyamide/

WEIGHT: 43-45 g/m2.

TECHNICAL DATA

FINISH:

COLORS:

SOLIDS CONTENT :

DENSITY:

FLASH POINT:

VISCOSITY:

DRYING TIME:

PACKING: Rolls:
Width 8 inches (20cm) Length 325 feet (100m)
Width 20 inches (60cm) Length 325 feet (100m)
Width 46 inches (120cm) Length 325 feet (100m)



| | |
|----------------------------|-----------------|
| PRODUCT DATA SHEET | Page 2of 2 |
| | Revision: 2 US |
| RD-FLEECE OCTAGONAL | Date: 2/15/2007 |
| | |

STORAGE STABILITY: Unlimited.

TEST DATA: Available upon request.

SAFETY DATA

The Material Safety Data Sheet is available on request.

These specifications are given for information. Since the manufacturer is not able to check the correct application of the products, they cannot accept any responsibility for it. This technical data sheet replaces all previous editions.